

Flat

Design by Ichiro Iwasaki.

Reference

5950.

Application

Floor Lamps

Installation type

Surface mounted

Description

The Flat floor lamp offers multiple functionalities; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

Diffuser

Polycarbonate diffuser

Materials

Body: Steel

Base: Steel

Head: Aluminum


Reflector: Aluminum

Finishes



5950-10 White (NCS S 0300-N)

Sketch



Electrical characteristics

1 x LED PLATE 7W 400mA



Total 7.0 W

VIBIA



Light source: 2700K CRI >90 1200 lm 171 lm/W

Fixture: 455 lm 51.15 lm/W

Driver included: 400 mA 100~240V

Electronic dimming: PUSH


Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Certificates



Flat

Design by Ichiro Iwasaki.

Reference

5945.

Application

Floor Lamps

Installation type

Surface mounted

Description

The Flat floor lamp offers multiple functionalities; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

Diffuser

Polycarbonate diffuser

Materials

Body: Steel
Base: Steel
Head: Aluminum
Reflector: Aluminum

Finishes




5945-13 Grey L1 (NCS S 1000-N)



5945-47 Green L1 (NCS S 4005-G80Y)

Sketch



Electrical characteristics

2 x LED PLATE 7W 400mA



Total 14.0 W

VIBIA



Light source: 2700K CRI >90 2400 lm 171 lm/W

Driver included: CC - Constant Current 400 mA 100~240V 50/60Hz

Electronic dimming: PUSH


Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Certificates

